



TECHNICAL DATA SHEET  
**HE094 - CALSEAL CRACK FILLER**



Last Rev Date: 06/09/2004

**Physical Properties**

<b>Appearance</b> Solid at room temperature	<b>Flash Point</b> >390° F.	<b>Resiliency</b> 40-68% @ 77° F. (ASTM D-3407)
<b>Asphalt By Weight</b> 60-64 % (ASTM D-4)	<b>Flow @ 140° F</b> 0-3 mm (ASTM D3407)	<b>Softening Point</b> 195° F to 205° F.
<b>Color</b> Black	<b>Freezability</b> Will not freeze	<b>Specific Gravity @ 77° F</b> 1.17
<b>Cone Pen Viscosity</b> 20-50 dmm (ASTM D-3407)	<b>Maximum VOC</b> 0 calculated	<b>Weight Per Gallon</b> 9.7-9.8 lbs
<b>Ductility @ 77° F, 5cm/min</b> 30-38 cm (ASTM-D-113)	<b>Maximum VOS</b> 0 calculated	<b>Weight Per Gallon Calculated</b> 9.75 lbs

**Description**

HE094 - CALSEAL CRACK FILLER is a mixture of paving asphalt and ground rubber or ground rubber and polymer which conforms to the above requirements.

**Usage**

HE094 - CALSEAL CRACK FILLER is used for sealing cracks in asphaltic and concrete highways, city streets, and rural roadways.

**Coverage**

HE094 - CALSEAL CRACK FILLER comes in 35 lb boxes (1 block per box)

**Surface Preparation**

Surface must be dry and free from all loose material, dirt, and dust. Any weeds or plant matter should be removed and the area sprayed with herbicide. Routing is optional.

**Application**

HE094 - CALSEAL CRACK FILLER can be melted and applied to cracks and joints at temperatures below 400° F. When heated, HE094 - CALSEAL CRACK FILLER will readily penetrate cracks 1/4" wide or larger. Cracks can be filled flush or may be over filled and squeegeed. HE094 - CALSEAL CRACK FILLER can be applied using a pressure feed wand system or with a pour pot.

**Precautions**

Do not allow material to exceed 400° F.

**Cleanup**

Asphalt can be cleaned with mineral spirits. Otherwise it can be cleaned with waterless hand cleaner and water.

## Caution

Keep boxes out of direct sunlight and rain. (If covered area is not accessible, cover with tarp).

**CAUTION!** Close container after each use. **DO NOT TAKE INTERNALLY!** Use protective measures to avoid contact with eyes and skin. **If swallowed, CALL PHYSICIAN IMMEDIATELY!** **In case of eye contact**, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **In case of accidental injection** by power spray equipment, **GET MEDICAL ATTENTION IMMEDIATELY!** Dispose of container and unused contents in accordance with Local, State, and Federal regulations. **KEEP OUT REACH OF CHILDREN. KEEP FROM FREEZING.**

**WARNING:** This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

**EMPLOYERS** should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

## Product Sizes

35 lbs box

## Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product--such as weather, workmanship, equipment utilized, and prior condition of the substrate--are beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommend as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES:** The Limited Warranty is **IN LIEU OF** any other warranties express or implied including but not limited to any implied warranty of **MERCHANTABILITY** or fitness for a particular purpose; and we, the manufacturer, shall have no further liability of any kind including liability for consequential or incidental damages resulting from any defects or any delays caused by replacement or otherwise