

Two ways to save...

OVERKOTE Oil-Spot Seal

OVERKOTE **PLUS** Pavement Coating Additive

Over
Kote ✓

A Product of

**REED &
GRAHAM
INC.**



OverKote Oil-Spot Seal

OverKote Oil-Spot Seal is a quick drying latex emulsion formulated with suitable additives to coat and promote adhesion over oil, grease and gasoline spots prior to the application of OverKote asphalt sealer on asphaltic surfaces. It is easy to use on parking lots, driveways, or any asphalt surface.

Application

Prior to application, the surface area to be treated must be free of dirt and dust. Scrape and remove excessive build-up of oil or grease before applying



product. OverKote Oil-Spot Seal should be diluted 1 to 1 (50%) with potable water. OverKote Oil-Spot Seal may be applied with either a sprayer or brush. Mix OverKote Oil-Spot Seal well before using. Sprinkle a slight amount of silica sand on the OverKote Oil-Spot Seal to improve adhesion. Wash all tools in water. Keep from freezing. Do not store in direct sunlight. Container should be closed when not in use. Keep out of the reach of children.

OverKote Oil-Spot Seal is available in five gallon pails and 50 gallon drums.



OverKote Plus—Pavement Coating Additive

OverKote Plus is a specially blended copolymer emulsion along with effective chemical resistance additives to modify asphalt emulsion sealer to achieve outstanding toughness, color enhancement, faster curing time, greater flexibility, high viscosity, good suspension of the aggregates. It is recommended on any asphalt surface where there are high traffic patterns. Excellent for commercial and industrial parking lots, airport runways, traffic safety islands and service stations.

Mixture

Mix well before using. Use 1 to 5 gallons of OverKote Plus undiluted, to modify 100 gallons of asphalt emulsion sealer. The amount will vary depending on the end use in the traffic pattern or specifications.

Application

Prior to applying "modified" OverKote sealer, surface must be clean, free from dirt, dust and oil. Treat oil, grease and gasoline spots with OverKote Oil-Spot Seal.

Always pour sealer into mechanical applicator or squeegee type machine first, then add proper amount of water. When agitating, add OverKote Plus slowly and mix to a uniform consistency. After mixing add the proper amount of aggregates (silica, sand, or any other specified aggregates) and mix thoroughly before application.

Wash all tools in water or use a suitable paint thinner if material has dried. Keep from freezing. Do not store in direct sunlight. Container should be closed when not in use. Keep out of the reach of children.

OverKote Plus is available in five gallon pails and 50 gallon drums.

Due to the wide range of variables affecting the results of application, such as weather conditions, construction equipment, and quality of other materials, there is no warranty, expressed or implied that following this specification, or using the materials covered thereby, will assure satisfactory results.

A Product of



®

BAY AREA
690 Sunol Street
San Jose, CA
95126
Fax 408/294-3696
408/287-1400



Asphalt Pavement Coating, Crack Filler, Induction Loop Filler,
Oil-Spot Seal, Plus—Pavement Coating Additive, Bumper Adhesive