

## RG COIR 900 EROSION CONTROL BLANKET

Coir Geotextiles are a range of woven open mesh fabrics made from 100% natural and biodegradable Coir nettings installed on the surface to hold seed and soil intact during the establishment of vegetative cover. When it biodegrades, it will add organic nutrients to the soil. Coir Geotextiles are "Environmentally Friendly" products.

Property	Test Method	Typical Value
Weight/Unit Area g/m <sup>2</sup> (oz/yd <sup>2</sup> )	ASTM-3776C	900 (26.6)
Open Area %	--	39
Wide width Tensile, Dry kN/m (lb/in) warp x fill	ASTM D 4595	27.8 x 9.3 (112 x 54)
Wide width Tensile, Wet kN/m (lb/in) warp x fill	ASTM D 4595	21.4 x 6.8 (86 x 41)
Elongation at Failure, Dry % warp x fill	ASTM 4595	68 x 32
Elongation at Failure, Wet % warp x fill	ASTM 4595	82 x 49
Maximum Shear Stress N/m <sup>2</sup> (lb/ft <sup>2</sup> )	--	221.69 (4.63)
Chezy-Manning's Coefficient of Roughness	--	0.0334
"C" Factor, 1.5:1 slope	--	0.002
Water Flow Velocity m/sec (ft/sec)	--	4.6 (15)

Roll Size	Area (metric)	Area (English)
2 M x 50 M (6.56 ft x 165 ft)	100 square meters	120 square yards
4 M x 50 M (13.1 ft x 165 ft)	200 square meters	240 square yards

Disclaimer: Reed & Graham, Inc. assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Reed & Graham, Inc. disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.